



- NOTES:
- i ROLLED THREADS
 - ii U-BOLTS TO BE ELECTROGALVANISED
 - iii U-BOLTS TO BE SUPPLIED COMPLETE WITH M10x1.5 NYLOCK NUTS

REV	DESCRIPTION OF CHANGE	ZONE	AUTH NO.	BY	DATE
P4	CORRECTED CENTER DISTANCE FROM 48mm TO 58mm		H.M.	H.M.	2010-02-03
P3	CHANGED MATERIAL TO 8.8 HIGH TENSILE FROM MILD STEEL		H.M.	H.M.	2002-06-01
P2	CHANGED PRODUCT CODE AND DRAWING NUMBER		H.M.	H.M.	2002-03-11
P1	CHANGED MATERIAL FROM 8.8 HIGH TENSILE TO MILD STEEL		H.M.	H.M.	2001-05-04

© BURQUIP INTERNATIONAL (Pty) Ltd

ASSUME A TOLERANCE OF ±1mm FOR DIMENSIONS WITHOUT TOLERANCES ALL DIMENSIONS IN mm UNLESS OTHERWISE SHOWN

8.8 HIGH TENSILE		ø8.9mm	
MATERIAL DESCRIPTION		MATERIAL SIZE	
TITLE:			
PRODUCT: U-BOLT 40mm SQUARE		BURQUIP	
SCALE: 1:1	SHEET: A3	DRAWING NO.	
DRAWN BY: HILTON MILLWARD		SU40S	
DATE: 1998-10-15		REV P3	